



**Faculty of Manufacturing Engineering**

**DEVELOP MATHEMATICAL MODEL FOR BIOMECHANICAL  
FACTORS FOR PROTON SAGA DRIVER SEAT**

Nur Sabrina Binti Mohd Yusoff

Master of Manufacturing Engineering (Industrial Engineering)

2020

## DECLARATION

I declare that this thesis entitled “Develop Mathematical Model for Biomechanical Factors for Proton Saga Driver Seat” is the result of my own research except as cited in reference. The thesis has not accepted for any degree and is not concurrently submitted in candidate of any other degree.



Signature :


Author's Name : NUR SABRINA BINTI MOHD YUSOFF

Date : 5 OCTOBER 2020

## APPROVAL

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of Master of Manufacturing Engineering (Industrial Engineering).

Signature :



Supervisor Name: Prof Madya Dr Seri Rahayu Kamat

## **DEDICATION**

For my beloved parents:

Mr. Mohd Yusoff Bin M.K. Mohd Mydin

Mrs. Najiya Binti Anwar Ali

To my beautiful sisters:

Nurhanna Binti Mohd Yusoff

Nur Farhana Binti Mohd Yusoff

To my supportive Supervisors and friends:

PM Dr. Seri Rahayu Kamat

Dr. Syamimi Binti Shamsuddin

Ms. Sharifah Nadya Binti Syed Azmi

Mohammad Firdaus Ani

Siti Najihah Binti Zainal Rashid

Nur Alya Syaherah Binti Mohd Hassan

## **ABSTRACT**

Automotive industry is the main industrial that leading in Malaysia development towards achieving Industrial Revolution 4.0. Safety will be their very first priority while manufacturing a car. During manufacturing process, external and internal components should be comply with the standard that have been set up by the authority. The most important components for the driver will be their seat. Upon driving for a long journey, drivers tend to feel weak and fatigue as time pass by. As a result, this could lead to accidents. Therefore, aim of the study is to develop mathematical modeling based on the psychophysical and biomechanical factors that contribute to the driver fatigue of Proton Saga. The discomfort area will be investigate through online survey and validate using Minitab software. Meanwhile, as for the relationship of the psychophysical and biomechanical will be analyze by simulator and real road conditions also determine the hardness of the seat foam. Based on obtain parameters, the regression analysis will develop and validate the mathematical model for Proton Saga driver seat as the benefits of mathematical modelling able to simplify complex situations and helps our understanding the real world as certain variables can readily be changed.

# **MEMBINA MODEL MATEMATIK UNTUK FAKTOR BIOMEKANIKAL UNTUK KERETA PEMANDU PROTON SAGA**

## **ABSTRAK**

Industri automotif adalah industri utama yang memimpin pembangunan Malaysia ke arah mencapai Revolusi Industri 4.0. Keselamatan akan menjadi keutamaan pertama mereka semasa membuat kereta. Semasa proses pembuatan, komponen luaran dan dalaman harus mematuhi standard yang telah ditetapkan oleh pihak berkuasa. Komponen yang paling penting bagi pemandu adalah tempat duduknya. Setelah memandu untuk perjalanan jauh, pemandu cenderung merasa lemah dan keletihan seiring berjalannya waktu. Akibatnya, ini boleh menyebabkan kemalangan. Oleh itu, tujuan kajian adalah untuk mengembangkan pemodelan matematik berdasarkan faktor psikofizik dan biomekanik yang menyumbang kepada keletihan pemandu Proton Saga. Kawasan ketidakselesaan akan disiasat melalui tinjauan dalam talian dan mengesahkan menggunakan perisian Minitab. Sementara itu, untuk hubungan psikofizik dan biomekanik akan dianalisis oleh simulator dan keadaan jalan sebenar juga menentukan kekerasan busa tempat duduk. Berdasarkan parameter perolehan, analisis regresi akan mengembangkan dan mengesahkan model matematik untuk tempat duduk pemandu Proton Saga kerana faedah pemodelan matematik dapat mempermudah situasi yang kompleks dan membantu kita memahami dunia nyata kerana pemboleh ubah tertentu dapat dengan mudah diubah.

## **ACKNOWLEDGEMENT**

First of all, I would like to praise to Almighty Allah SWT for giving me the opportunity and spirit to complete my research. I also would like to express my gratitude to my beloved parents, Mr. Mohd Yusoff and Mrs. Najiya for the continuous supportive and funding. Without their blessings, I would not make it to this far.

I would also like to thanks my Supervisors, Associate Professor Dr. Seri Rahayu Kamat and Dr. Syamimi Binti Shamsuddin who excellently guide me, advices me throughout completing this project and also motivates me in a good way which makes me improve in this project.

Not to forget my Industrial Supervisor, Mrs. Sharifah Nadya Binti Syed Azmi for considering me as an Industrial Trainee and give me the opportunity for me involved in Proton Project at Proton Holdings Bhd

Last but not least, my respect to Mohammad Firdaus Ani, Siti Najihah and Nur Alya Syaherah for encouraging me throughout this project.

# TABLE OF CONTENT

	PAGE
DECLARATION	
APPROVAL	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	xii
LIST OF ABBREVIATIONS	xvi
CHAPTER	
1 INTRODUCTION	1
1.1 Background of study	1
1.2 Problem Statement	2
1.3 Research Objectives	6
1.4 Research Scope	6
1.5 Significant of study	7
2 LITERATURE REVIEW	8
2.1 Ergonomics in Automotive Industry	8
2.1.1 Comfort	9
2.1.2 Safety	9
2.1.3 Ease of Use	11
2.1.4 Productivity or Performance	11
2.2 Psychophysical	12
2.2.1 Factors contributed to road accident	12
2.2.2 Psychological Factors	13
2.2.2.1 Motivation	13
2.2.2.2 Personality	14
2.2.2.3 Cognitive style	14
2.3 Biomechanical	14



2.3.1	Male versus female strength	15
2.3.2	Effect of age	15
2.3.3	Muscular contraction	15
2.3.4	Endurance time and strength trade-off	16
2.3.5	Third class of lever	16
2.3.6	Design loads	16
2.4	Seat pressure distribution	17
2.4.1	Weight related to pressure distribution	17
2.4.2	Hardness related to pressure distribution	18
2.4.3	Contact area	19
2.5	Driving Fatigue	20
2.6	Mathematical Model	21
2.6.1	Regression Analysis	31
2.7	Summary	31
2.7.1	Table of Summary	32
<b>3</b>	<b>METHODOLOGY</b>	<b>36</b>
3.1	Identifying the relationship between Objectives and Method	36
3.2	Proton Saga	37
3.3	Assessment for Postural Discomfort Factors	38
3.3.1	Minitab Software	40
3.4	Assessment for Pressure Distribution Factors by Experiment	41
3.4.1	Equipment's for Analyzing Pressure Seat Distribution	45
3.5	Assessment for Pressure Distribution Factors by Survey	45
3.6	Compression test	46
3.7	Variables	48
3.8	Design Expert 7.0.0	48
3.8.1	Regression Analysis	49
3.8.2	Expected Result	50
3.9	Summary	51
<b>4</b>	<b>RESULT AND DISCUSSION</b>	<b>52</b>
4.1	Respondent Background	52
4.1.1	Age	53
4.1.2	Weight (kg)	53
4.1.3	Height (cm)	54
4.1.4	Experience of driving	55
4.1.5	History of accident	55
4.1.6	Medical record	56

4.2	Comfort Level	57
4.2.1	Distance travel	57
4.2.2	Postural Discomfort	57
4.2.3	Postural (upper part)	58
4.2.4	Postural (lower part)	59
4.2.5	Factors of discomfort	61
4.2.6	Design of car seat	61
4.2.7	Comfortable seat	62
4.3	Psychological Test	62
4.3.1	Neck	63
4.3.2	Shoulder	63
4.3.3	Upper Arms	64
4.3.4	Lower Arms	64
4.3.5	Upper Back	65
4.3.6	Mid Back	65
4.3.7	Lower Back	66
4.3.8	Buttocks	66
4.3.9	Thighs	67
4.3.10	Legs	67
4.4	Minitab Software	68
4.5	Anthropometric Data Measurement of Respondents	68
4.6	Pressure Distribution Area on Different Types of Road	71
4.6.1	Pressure Distribution for Proton Saga Cushion Seat	73
4.6.2	Pressure Distribution for Backrest of Proton Saga	74
4.7	Hardness of Proton Saga Seat Cushion	76
4.8	Post Survey for Proton Saga	79
4.9	Modelling of Biomechanical for Proton Saga Driver's Seat	85
4.9.1	Regression Model of Biomechanical Factor for Cushion Seat (Force,N)	85
4.9.1.1	5 <sup>th</sup> Percentiles for Cushion Seat	85
4.9.1.2	50 <sup>th</sup> Percentiles for Cushion Seat	89
4.9.1.3	95 <sup>th</sup> Percentiles for Cushion Seat	93
4.9.2	Regression Model of Biomechanical Factor for Cushion Seat (Pressure,kPa)	96
4.9.2.1	5 <sup>th</sup> Percentiles for Cushion Seat	97
4.9.2.2	50 <sup>th</sup> Percentiles for Cushion Seat	101
4.9.2.3	95 <sup>th</sup> Percentiles for Cushion Seat	105

4.9.3	Regression Model of Biomechanical Factor for Cushion Seat (Contact Area, mm <sup>2</sup> )	108
4.9.3.1	5 <sup>th</sup> Percentiles for Cushion Seat	109
4.9.3.2	50 <sup>th</sup> Percentiles for Cushion Seat	113
4.9.3.3	95 <sup>th</sup> Percentiles for Cushion Seat	117
4.9.4	Regression Model of Biomechanical Factor for Backrest (Force,N)	120
4.9.4.1	5 <sup>th</sup> Percentiles for Backrest	121
4.9.4.2	50 <sup>th</sup> Percentiles for Backrest	125
4.9.4.3	95 <sup>th</sup> Percentiles for Backrest	129
4.9.5	Regression Model of Biomechanical Factor for Backrest (Pressure,kPa)	133
4.9.5.1	5 <sup>th</sup> Percentiles for Backrest	134
4.9.5.2	50 <sup>th</sup> Percentiles for Backrest	138
4.9.5.3	95 <sup>th</sup> Percentiles for Backrest	142
4.9.6	Regression Model of Biomechanical Factor for Backrest (Contact Area, mm <sup>2</sup> )	145
4.9.6.1	5 <sup>th</sup> Percentiles for Backrest	146
4.9.6.2	50 <sup>th</sup> Percentiles for Backrest	150
4.9.6.3	95 <sup>th</sup> Percentiles for Backrest	154
4.9.7	General Formula Developed for Cushion for Proton Saga Driver's Seat	158
4.9.8	Validation of the Mathematical Modelling for Cushion Seat and Backrest	160
4.9.8.1	Validation of Cushion Seat	160
4.9.8.2	Validation of Backrest	162
4.9.9	Summarization of Regression Modelling	164
4.9.9.1	Summarization of Cushion Seat Proton Saga Driver Seat	164
<b>5</b>	<b>CONCLUSION AND RECOMMENDATION</b>	<b>167</b>
5.1	Conclusion	167
5.2	Implication of Study	167
5.3	Recommendation of Future Work	168

# LIST OF TABLES

Table 1.1: Statistic by MIROS	3
Table 2.1: Two division in Developing Mathematical Model	22
Table 3.1: Relationship between objectives and methods	37
Table 3.2: Percentiles range of stature	43
Table 3.3: Anthropometric Measurement Data for all Percentiles	45
Table 3.4: Expected Result in This Research	50
Table 4.1: Anthropometric Measurement Data for 5th Percentiles	70
Table 4.2: Anthropometric Measurement Data for 50th Percentiles	70
Table 4.3: Anthropometric Measurement Data for 95th Percentiles	71
Table 4.4: Maximum pressure distribution for cushion seat model Proton Saga	73
Table 4.5: Maximum pressure distribution for backrest model Proton Saga	74
Table 4.6: Parameters for Proton Saga model	77
Table 4.7: Stress versus Strain Data for Proton Saga	78
Table 4.8: Post Survey for Proton Saga	79
Table 4.9: Average Response for 5 <sup>th</sup> Percentiles Force	86
Table 4.10: SMSS for 5 <sup>th</sup> Percentiles force	86
Table 4.11: ANOVA analysis of the 2FI model for 5 <sup>th</sup> percentiles force	87
Table 4.12: Polynomial equation for the force for 5 <sup>th</sup> percentiles model in terms of actual factors	87
Table 4.13: Average Response for 50th Percentiles Force	89
Table 4.14: SMSS for 50th Percentiles force	89
Table 4.15: ANOVA analysis of the 2FI model for 50th percentiles force	90
Table 4.16: Polynomial equation for the force for 50th percentiles model in terms of actual factors	91
Table 4.17: Average Response for 95th Percentiles Force	93
Table 4.18: SMSS for 95th Percentiles force	93
Table 4.19: ANOVA analysis of the 2FI model for 95th percentiles force	94

Table 4.20: Polynomial equation for the force for 95th percentiles model in terms of actual factors	95
Table 4.21: Average Response for 5th Percentiles Pressure	97
Table 4.22: SMSS for 5th Percentiles pressure	97
Table 4.23: ANOVA analysis of the 2FI model for 5th percentiles pressure	98
Table 4.24: Polynomial equation for the pressure for 5th percentiles model in terms of actual factors	99
Table 4.25: Average Response for 50th Percentiles Pressure	101
Table 4.26: SMSS for 50th Percentiles pressure	101
Table 4.27: ANOVA analysis of the 2FI model for 50th percentiles pressure	102
Table 4.28: Polynomial equation for the pressure for 50th percentiles model in terms of actual factors	103
Table 4.29: Average Response for 95th Percentiles Pressure	105
Table 4.30: SMSS for 95th Percentiles pressure	105
Table 4.31: ANOVA analysis of the 2FI model for 95th percentiles pressure	106
Table 4.32: Polynomial equation for the pressure for 95th percentiles model in terms of actual factors	107
Table 4.33: Average Response for 5th Percentiles Contact Area	109
Table 4.34: SMSS for 5th Percentiles contact area	109
Table 4.35: ANOVA analysis of the 2FI model for 5th percentiles contact area	110
Table 4.36: Polynomial equation for the contact area for 5th percentiles model in terms of actual factors	111
Table 4.37: Average Response for 50th Percentiles Contact Area	113
Table 4.38: SMSS for 50th Percentiles contact area	113
Table 4.39: ANOVA analysis of the 2FI model for 50th percentiles contact area	114
Table 4.40: Polynomial equation for the contact area for 50th percentiles model in terms of actual factors	115
Table 4.41: Average Response for 95th Percentiles Contact Area	117
Table 4.42: Table 4.38: SMSS for 95th Percentiles contact area	117
Table 4.43: ANOVA analysis of the 2FI model for 95th percentiles contact area	118
Table 4.44: Polynomial equation for the contact area for 95th percentiles model in terms of actual factors	119
Table 4.45: Average Response for 5th Percentiles Force	121
Table 4.46: Table 4.42: Table 4.38: SMSS for 5th Percentiles force	121

Table 4.47: ANOVA analysis of the 2FI model for 5th percentiles force	122
Table 4.48: Polynomial equation for the force for 5th percentiles model in terms of actual factors	123
Table 4.49: Average Response for 50th Percentiles Force	125
Table 4.50: SMSS for 50th Percentiles force	125
Table 4.51: ANOVA analysis of the 2FI model for 50th percentiles force	126
Table 4.52: Polynomial equation for the force for 50th percentiles model in terms of actual factors	127
Table 4.53: Average Response for 95th Percentiles Force	129
Table 4.54: Table 4.38: SMSS for 95th Percentiles force	129
Table 4.55: ANOVA analysis of the 2FI model for 95th percentiles force	130
Table 4.56: Polynomial equation for the force for 95th percentiles model in terms of actual factors	131
Table 4.57: Average Response for 5th Percentiles Pressure	134
Table 4.58: SMSS for 5th Percentiles pressure	134
Table 4.59: ANOVA analysis of the 2FI model for 5th percentiles pressure	135
Table 4.60: Polynomial equation for the pressure for 5th percentiles model in terms of actual factors	136
Table 4.61: Average Response for 50th Percentiles Pressure	138
Table 4.62: SMSS for 50th Percentiles pressure	138
Table 4.63: ANOVA analysis of the 2FI model for 50th percentiles pressure	139
Table 4.64: Polynomial equation for the pressure for 50th percentiles model in terms of actual factors	140
Table 4.65: Average Response for 95th Percentiles Pressure	142
Table 4.66: SMSS for 95th Percentiles pressure	142
Table 4.67: ANOVA analysis of the 2FI model for 95th percentiles pressure	143
Table 4.68: Polynomial equation for the pressure for 95th percentiles model in terms of actual factors	144
Table 4.69: Average Response for 5th Percentiles Contact Area	146
Table 4.70: SMSS for 5th Percentiles contact area	146
Table 4.71: ANOVA analysis of the 2FI model for 5th percentiles contact area	147
Table 4.72: Polynomial equation for the contact area for 5th percentiles model in terms of actual factors	148
Table 4.73: Average Response for 50 <sup>th</sup> Percentiles Contact Area	150

Table 4.74: SMSS for 50 <sup>th</sup> Percentiles contact area	150
Table 4.75: ANOVA analysis of the 2FI model for 50th percentiles contact area	151
Table 4.76: Polynomial equation for the contact area for 50th percentiles model in terms of actual factors	152
Table 4.77: Average Response for 95th Percentiles Contact Area	154
Table 4.78: SMSS for 95th Percentiles contact area	154
Table 4.79: ANOVA analysis of the 2FI model for 95th percentiles contact area	155
Table 4.80: Polynomial equation for the contact area for 95th percentiles model in terms of actual factors	156
Table 4.81: General Formula for Cushion Seat	158
Table 4.82: General Formula for Backrest	159
Table 4.83: 5th Percentiles (Force)	160
Table 4.84: 5th Percentiles (Pressure)	160
Table 4.85: 5th Percentiles (Contact Area)	160
Table 4.86: 50th Percentiles (Force)	160
Table 4.87: 50th Percentiles (Pressure)	161
Table 4.88: 50th Percentiles (Contact Area)	161
Table 4.89: 95th Percentiles (Force)	161
Table 4.90: 95th Percentiles (Pressure)	161
Table 4.91: 95th Percentiles (Contact Area)	161
Table 4.92: 5th Percentiles (Force)	162
Table 4.93: 5th Percentiles (Pressure)	162
Table 4.94: 5th Percentiles (Contact Area)	162
Table 4.95: 50th Percentiles (Force)	162
Table 4.96: 50th Percentiles (Pressure)	162
Table 4.97: 50th Percentiles (Contact Area)	163
Table 4.98: 95th Percentiles (Force)	163
Table 4.99: 95th Percentiles (Pressure)	163
Table 4.100: 95th Percentiles (Contact Area )	163
Table 4.101: Summarization of Cushion Seat	164
Table 4.102: Summarization of Backrest	165

# LIST OF FIGURES

Figure 1.1: Statistic by MIROS	4
Figure 1.2: Factors of discomfort while driving	5
Figure 1.3: World Health Organization	5
Figure 2.1: Global information and communication technology development	10
Figure 2.2: Theoretical Motivational Model	13
Figure 2.3: Safety critical event involvement by BMI 009	18
Figure 2.4: Load versus deflection	18
Figure 2.5: Cushion material	19
Figure 2.6: Result for sitting posture and anal triangle	20
Figure 2.7: Standard Deviation of Lateral Mathematical Model	21
Figure 3.1: Flowchart for Postural Discomfort Factors	38
Figure 3.2: Image Assessing Postural Discomfort	39
Figure 3.3: Flowchart for Pressure Distribution Factor (Experiment)	41
Figure 3.4 : Driving Simulator with Proton Saga seat	42
Figure 3.5 : Interior Dimension of Proton Saga	42
Figure 3.6: Anthropometer	44
Figure 3.7: Measuring Tape	44
Figure 3.8: Measurements of body parts	44
Figure 3.9: Flowchart for Postural Discomfort Factor (Survey)	46
Figure 3.10: Hardness Test procedure	47
Figure 3.11: Process Flow in Design Expert	49
Figure 3.12: Summary of Regression Analysis	50
Figure 4.1: Gender statistics	52
Figure 4.2: Age statistics	53
Figure 4.3: Weight of respondents (kg)	54
Figure 4.4: Height of the respondents (cm)	54
Figure 4.5: Experience of driving by respondents	55
Figure 4.6: History of accidents	55



Figure 4.7: Record of accidents	56
Figure 4.8 : Medical Record	56
Figure 4.9: Distance travel of driver	57
Figure 4.10: Postural Discomfort	58
Figure 4.11: Upper part	59
Figure 4.12: Lower part	60
Figure 4.13: Factors lead to discomfort while driving	61
Figure 4.14: Design for seat	61
Figure 4.15: Preferred car seat design	62
Figure 4.16: Postural discomfort	62
Figure 4.17: Neck Fatigue	63
Figure 4.18: Shoulder Fatigue	63
Figure 4.19: Upper Arms fatigue	64
Figure 4.20: Lower Arms fatigue	64
Figure 4.21: Upper Back fatigue	65
Figure 4.22: Mid Back fatigue	65
Figure 4.23: Lower Back fatigue	66
Figure 4.24: Buttocks fatigue	66
Figure 4.25: Thighs fatigue	67
Figure 4.26: Legs fatigue	67
Figure 4.27: Cronbach's Alpha	68
Figure 4.28: Part C validation	68
Figure 4.29: Anthropometer	69
Figure 4.30: Measuring Tape	69
Figure 4.31: Measurements of body parts	69
Figure 4.32: Area of one box	72
Figure 4.33: Slotted weight with mass of 5N	76
Figure 4.34: Proton Saga post survey	77
Figure 4.35: Graph for Proton Saga Model	78
Figure 4.36: Behavior of response factor (force) to interaction between type of road on time.	88
Figure 4.37: Behavior of response (force) to interaction between type of road and gender	88
Figure 4.38: Behavior of response (force) to variation in time	91

Figure 4.39: Behavior of response (force) to variation in gender	92
Figure 4.40: Behavior of response (force) to variation in type of road	92
Figure 4.41: Behavior of response (force) to variation in time	95
Figure 4.42: Behavior of response (force) to variation in type of road	96
Figure 4.43: Behavior of response (force) to variation in gender	96
Figure 4.44: Behavior of response (pressure) to interaction between type of road and time	99
Figure 4.45: Behavior of response (pressure) to interaction between type of road and gender	100
Figure 4.46: Behavior of response (pressure) to interaction between type of road and time	104
Figure 4.47: Behavior of response (pressure) to interaction between type of road and gender	104
Figure 4.48: Behavior of response (pressure) to variation in time	107
Figure 4.49: Behavior of response (pressure) to variation in type of road	108
Figure 4.50: Behavior of response (pressure) to variation in gender	108
Figure 4.51: Behavior of response (pressure) to interaction between type of road and time	111
Figure 4.52: Behavior of response (pressure) to interaction between type of road and gender	112
Figure 4.53: Behavior of response (contact area) to variation in time	115
Figure 4.54: Behavior of response (contact area) to variation in type of road	116
Figure 4.55: Behavior of response (contact area) to variation in gender	116
Figure 4.56: Behavior of response (contact area) to interaction between type of road and time	119
Figure 4.57: Behavior of response (contact area) to interaction between type of road and gender	120
Figure 4.58: Behavior of response (force) to interaction between type of road and time	123
Figure 4.59: Behavior of response (force) to interaction between type of road and gender	124
Figure 4.60: Behavior of response (force) to interaction between type of road and time	127

Figure 4.61: Behavior of response (force) to interaction between type of road and gender	128
Figure 4.62: Behavior of response (force) to variation in time	131
Figure 4.63: Behavior of response (force) to variation in type of road	132
Figure 4.64: Behavior of response (force) to variation in gender	132
Figure 4.65: Behavior of response (pressure) to variation in time	136
Figure 4.66: Behavior of response (pressure) to variation in type of road	137
Figure 4.67: Behavior of response (pressure) to variation in gender	137
Figure 4.68: Behavior of response (pressure) to variation in time	140
Figure 4.69: Behavior of response (pressure) to variation in type of road	141
Figure 4.70: Behavior of response (pressure) to variation in gender	141
Figure 4.71: Behavior of response (pressure) to variation in time	144
Figure 4.72: Behavior of response (pressure) to variation in type of road	145
Figure 4.73: Behavior of response (pressure) to variation in gender	145
Figure 4.74: Behavior of response (contact area) to variation in time	148
Figure 4.75: Behavior of response (contact area) to variation in type of road	149
Figure 4.76: Behavior of response (contact area) to variation in gender	149
Figure 4.77: Behavior of response (contact area) to variation in time	152
Figure 4.78: Behavior of response (contact area) to variation in type of road	153
Figure 4.79: Behavior of response (contact area) to variation in gender	153
Figure 4.80: Behavior of response (contact area) to interaction between type of road and time	156
Figure 4.81: Behavior of response (contact area) to interaction between type of road and gender	157

## **LIST OF ABBREVIATIONS**

PROTON	-	Perusahaan Otomobil Nasional Berhad
SUV	-	Sport Utility Vehicle
ANOVA	-	Analysis of Variance
EMG	-	Electromyography
ESC	-	Electronic Stability Control
LDW	-	Lane Departure Warning
IRF	-	Injury Risk Factor
ATP	-	Adenosine triphosphate
BMI	-	Body Mass Index
RSM	-	Response Surface Methodology

# CHAPTER 1

## INTRODUCTION

Chapter one introduces the background of study which will investigate to posture problems occurs in an automotive industry. On top of that, this chapter also comprises 5 sub-title which are the research background, problem statement, research objectives, research scope and significant of research.

### 1.1 Background of study

In this modern civilization, having a transportation is a must in order to travel from one place to another. Majority of the people own minimum a car in one house. As a Malaysian, automotive industry have been established in Malaysian since 7 May 1983 by the name of Perusahaan Otomobil Nasional Berhad (PROTON). There are few models manufacture by the company which are Proton Ertiga, Saga, Pesona, Perdana, Iriz, Suprima S, Preve and Exora. Currently, PROTON introduced its vey first Sport Utility Vehicle (SUV) model known as PROTON X70 collaborating with new partner Zhejiang Geely Holding Group.

Given all the layout, while manufacturing the cars safety has become their main concern. When it comes to safety it will be completely linked with its driver, passenger and people out there. Most of the citizen travel daily as to purchase daily groceries or doing outdoor activities by Swedish travel survey investigate by (Olsson, 2011). People tend to get tired and fatigue while driving for a long time. A research done by (Sammonds, Fray and Mansfield, 2017) prove that drivers feel fatigue or discomfort from 80 minutes to 110 minutes of driving. This linked to the psychophysical and biomechanical whereby effect to the posture and emotional state of the drivers.

Psychophysical related to the mental and emotional state of a person. There are several methods for investigating psychological factors such as anthropometric data collection,

electromyography (EMG) or user studies and observations. EMG may be used to assess muscle reaction to muscle simulation that helps identify neuromuscular irregularities by a nerve. For instance the person's tired and comfort level. Next, Biomechanical Factors can be described as the size, structure and mass properties of body parts, joints linking the body, muscles generating body movements, joint mobility, body mechanical reactions forcing fields and voluntary body movements when applying forces to external objects (Bhise & Vivek D., 2012). There were research done by (Bowden and Ragsdale, 2018) developed a mathematical model for truck drivers based on the fatigue with level of alertness.

Every seat in a car was built according to regulations. The distinction would be the scientific information that supports the design of a supportive car seat, and the impact of new technologies such as relaxation systems, neck rest, ultra-light seats, lumbar supports and seat shape is uncertain (M.Manfred, 2010). Some of the buyer might considered this factors during purchasing a car (Zenk & Raphael, 2008). Each driver have their own style or posture of seating whether seat comfortably , seat more to the right side or left side. This posture will lead to a pressure distribution reading. Seat pressure distribution known as the interface between human body and surface of the seat. There is, for example, a person sitting on the car seat and feeling squeezed under the lower body, such as hip. Because of the psychophysical and biomechanical factors, if the person feels discomfort as easy to feel pain at the boy's lower part and tired during their driving either close or long journey, it will affect the driver fatigue and tend to involve in accidents.

Therefore, this research propose a mathematical modelling based on the biomechanical factors Proton Saga driver seat.

## **1.2 Problem Statement**

This project is a collaboration together with PROTON Berhad specifically in Research and Development department (R&D). The main purpose of this project is to have a standard mathematical model to be used by Proton Saga model focusing for driver seat. After brainstorming together with Ergonomic Leader, a discussion have been made based on the customers complaint and standard requirements, that mathematical model developed as a guideline while designing the driver seat.

Zero number of accidents cannot be achieved however, as a person, they can reduce the number of accidents if it includes cars, bikes or even buses and lorries. Studies show that traffic accidents and road fatalities are on the rise from 2008 to 2017 (MIROS, 2018). Table 1.1 shows the statistic of road accidents in Malaysia from 2008 to 2017.

Table 1.1: Statistic by MIROS (MIROS, 2018)

NEGERI State	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017
PERLIS	1,417	1,633	1,548	1,791	1,881	1,895	1,888	1,861	2,062	1,925
KEDAH	16,520	17,701	17,966	19,699	19,935	20,228	20,159	22,016	23,200	23,262
PULAU PINANG	34,049	33,719	34,306	37,158	37,851	39,361	38,747	39,856	42,244	43,007
PERAK	30,539	32,327	32,072	33,506	34,714	35,408	35,131	36,736	38,531	38,587
SELANGOR	100,380	107,429	115,565	128,876	129,106	135,024	137,809	140,957	151,253	154,958
W.P. KUALA LUMPUR	48,671	51,942	53,493	58,795	61,872	64,527	63,535	64,664	68,866	72,940
NEGERI SEMBILAN	17,362	18,369	19,407	21,157	22,146	23,066	23,748	22,939	24,428	24,941
MELAKA	12,105	13,275	14,110	14,720	15,195	16,083	16,375	17,069	18,601	18,771
JOHOR	48,667	51,747	55,381	59,501	62,316	64,600	64,473	67,112	73,116	76,121
PAHANG	15,629	17,068	17,315	19,001	20,554	20,130	19,071	19,635	20,465	20,813
KELANTAN	8,842	9,549	9,707	9,603	9,968	9,748	10,326	9,960	10,544	10,786
TERENGGANU	8,814	10,118	10,106	10,684	10,861	10,996	9,383	10,381	10,793	10,713
SABAH	14,588	15,798	16,192	16,585	17,446	17,438	17,858	17,290	17,298	17,244
SARAWAK	15,488	16,655	17,253	17,964	18,578	18,700	17,693	19,130	20,065	19,807
JUMLAH Total	373,071	397,330	414,421	449,040	462,423	477,204	476,196	489,606	521,466	533,875

Meanwhile, a latest statistic developed by (Rohayu S, 2012) shows that based on the ARIMA model produced, the number of deaths is expected to increase to 8,760 (2015 year) and 10,716 (2020 year) respectively as illustrated in Figure 1.1 below.




Figure 1.1: Statistic by MIROS (Rohayu S, 2012)

From the above statistics, there are several causes of accidents that might occur during driving, such as feeling uncomfortable or back pain for a long journey, being tired, sleepy or reckless or ignoring traffic rules. According to World Health Organization, Malaysia has been ranked as one of the top three countries in the world deadliest roads (Ruxyn, 2017). On the other hand, there have been studies demonstrating a major relationship between emotion, personality characteristics, role modeling and the attitude of the driver towards safety (YII & Julia Lau Siew, 2015).

A pilot research was conducted in this research which distributed a survey for 40 respondents in order to measure the level of comfort. Figure 1.2 shows the data prove that the comfort factors while driving is poor body posture.